












Product	Feeder Capacity	Built In Ink Jet Endorser	Image Format	MICR	Exit Pockets	Scanning Speed	Built-In Jogger	PC Interface	Color/Greyscale	Output Resolution
<b>Canon CR-180</b> 	Automatic 200 Max.	Yes EBS	TIFF - JPG - BMP	E13B CMC7	Two - 200 each	180 @ 200dpi	Yes	SCSI / USBII	Color - No GS 16 - 256 Levels B/W	100 / 150 200 / 240 dpi
<b>Canon CR-55</b> 	Automatic 50 Max.	Yes EBS	TIFF - JPG - BMP	E13B CMC7	One - 50	55 @ 200dpi	No	USBII	Color - Yes GS 256 Level B/W	100 / 200 / 300 dpi
<b>Canon CR-25</b> 	Automatic 50 Max.	Yes EBS	TIFF - JPG - BMP	E13B CMC7	One - 50	25 @ 200dpi	No	USBII	Color - Yes GS 256 Level B/W	100 / 200 / 300 dpi
<b>Panini MyVision X-NJ</b> 	Automatic 30 (Standard) 100 (Upgrade)	No	TIFF - JPG - BMP	E13B CMC7	One - 30/100	30 Standard @ 200dpi 60 - 90 Upgradeable	No	USBII	Color - No GS 16 Level B/W	100 / 200 dpi
<b>Panini MyVision X-AGP</b> 	Automatic 30 (Standard) 100 (Upgrade)	Yes BMP & EBS	TIFF - JPG - BMP	E13B CMC7	One - 30/100	30 Standard @ 200dpi 60 - 90 Upgradeable	No	USBII	Color - No GS 16 Level B/W	100 / 200 dpi
<b>CTS LS-100</b> 	Manual Auto Feed Optional 15 Max.	No EBS Endorser Optional	TIFF - JPG - BMP	E13B CMC7	One - 15	52 @ 200dpi	No	USBII	Color - Yes GS 16/256 Level B/W	100 / 200 dpi
<b>CTS LS-515</b> 	Automatic 80 Max.	No EBS Endorser Optional	TIFF - JPG - BMP	E13B CMC7	Two - 50/50	120 @ 200dpi	No	SCSI / USBII	Color - Yes GS 16/256 Level B/W	100 / 200 dpi
<b>CTS LS-800</b> 	Automatic 500 Max.	No EBS Endorser Optional	TIFF - JPG - BMP	E13B CMC7	Three - 250 each Expandable to 22	200 @ 200dpi	No	USBII	Color - Yes GS 16/256 Level B/W	100 / 200 dpi
<b>Epson Capture One</b> 	Automatic 100 Max.	Yes EBS & Franking Standard	TIFF - JPG - BMP	E13B CMC7	Two 50/50	30 @ 200dpi 60 Upgradeable	No	USBII	Color - No GS 16 Level B/W	100 / 200 dpi